

CC 2600 Capacities on Superlift

SSL/LSL

360°

Capacity (t) = Load + Hook Block

Counterweight 149 t
Track 8 m

Main Boom 108.0 m Type 717-01/714-01/617-01

SL-Mast 30.0 m Type 617-01/612-02

Mast-Radius 15.6 m

SL-Cwt.-Radius 15.0 m

Radius (m)	Superlift-Counterweight (t)					
	0.0	50.0	100.0	150.0	200.0	250.0
16	108.0*	120.0*	-	-	-	-
18	90.0	120.0*	-	-	-	-
20	77.0	120.0*	-	-	-	-
22	66.0	105.0*	120.0*	-	-	-
24	57.0	92.0*	120.0*	-	-	-
26	49.0	81.0	113.0*	-	-	-
28	43.0	72.0	101.0*	120.0*	-	-
30	38.0	65.0	92.0*	118.0*	-	-
34	29.0	53.0	76.0	99.0*	-	-
38	22.0	44.0	64.0	84.0	105.0*	-
42	17.0	36.0	55.0	73.0	91.0	-
46	12.0	30.0	47.0	64.0	80.0	-
50	9.0	25.0	41.0	56.0	71.0	-
54	6.0	21.0	35.0	50.0	63.0	77.0
58	-	17.0	31.0	44.0	57.0	70.0
62	-	14.0	27.0	39.0	51.0	63.0
66	-	11.0	23.0	35.0	46.0	58.0
70	-	9.0	20.0	31.0	42.0	53.0
74	-	7.0	17.0	28.0	38.0	48.0
78	-	5.0	15.0	25.0	35.0	45.0
82	-	-	13.0	22.0	32.0	41.0
86	-	-	11.0	20.0	29.0	38.0
90	-	-	9.0	18.0	27.0	35.0
94	-	-	8.0	16.0	24.0	33.0

No. of Hoist Lines *2 x 5
1 x 7

	*2241	*2251	*2261	*2271	*2281	*2291
DS	2441	2451	2461	2471	2481	2491

DS = operating mode switch on PAT-console

* double hook block required

CC 2600 Capacities on Superlift

SSL/LSL

360°

Capacity (t) = Load + Hook Block

Counterweight 149 t
Track 8 m

Main Boom 120.0 m Type 717-01/714-01/617-01

SL-Mast 30.0 m Type 617-01/612-02

Mast-Radius 15.6 m

SL-Cwt.-Radius 15.0 m

Radius (m)	Superlift-Counterweight (t)					
	0.0	50.0	100.0	150.0	200.0	250.0
18	87.0	90.0*	-	-	-	-
20	73.0	90.0*	-	-	-	-
22	63.0	88.0*	-	-	-	-
24	54.0	85.0*	-	-	-	-
26	47.0	81.0*	82.0*	-	-	-
28	41.0	72.0	80.0*	-	-	-
30	36.0	65.0	77.0	-	-	-
34	27.0	52.0	72.0	-	-	-
38	21.0	43.0	64.0	-	-	-
42	16.0	36.0	54.0	64.0	-	-
46	12.0	29.0	47.0	60.0	-	-
50	8.0	24.0	40.0	55.0	-	-
54	5.0	20.0	35.0	49.0	-	-
58	-	16.0	30.0	43.0	51.0	-
62	-	13.0	26.0	39.0	48.0	-
66	-	10.0	22.0	34.0	46.0	-
70	-	8.0	19.0	30.0	41.0	-
74	-	6.0	16.0	27.0	37.0	-
78	-	-	14.0	24.0	34.0	40.0
82	-	-	12.0	21.0	31.0	39.0
86	-	-	10.0	19.0	28.0	36.0
90	-	-	8.0	17.0	25.0	34.0
94	-	-	7.0	15.0	23.0	31.0
98	-	-	5.0	13.0	21.0	29.0
102	-	-	-	12.0	19.0	27.0
106	-	-	-	10.0	17.0	25.0

No. of Hoist Lines *2 x 4
1 x 6

	*2242	*2252	*2262	*2272	*2282	*2292
DS	2442	2452	2462	2472	2482	2492

DS = operating mode switch on PAT-console * double hook block required