

CC 2600 Capacities on Main Boom

SH
----

360°

Capacity (t) = Load + Hook Block

Counterweight 129 t  
Track 6.9 m

Radius (m)	Main Boom (m)		Type 717-01/714-01				
	18.0	24.0	30.0	36.0	42.0	48.0	54.0
6	315.0**	358.0**	-	-	-	-	-
7	301.0**	342.0**	348.0**	347.0**	-	-	-
8	271.0*	269.0*	268.0*	267.0*	265.0*	264.0*	-
9	220.0*	218.0*	216.0*	215.0*	213.0*	212.0*	211.0*
10	184.0*	182.0*	181.0*	180.0*	178.0*	177.0*	176.0*
12	138.0	136.0	134.0	133.0	131.0	130.0	129.0
14	110.0	108.0	106.0	105.0	103.0	101.0	100.0
16	91.0	88.0	86.0	85.0	83.0	82.0	81.0
18	77.0	74.0	72.0	71.0	69.0	68.0	66.0
20	-	64.0	62.0	60.0	58.0	57.0	56.0
22	-	56.0	53.0	52.0	50.0	49.0	47.0
24	-	-	47.0	45.0	43.0	42.0	40.0
26	-	-	41.0	40.0	38.0	36.0	35.0
28	-	-	37.0	35.0	33.0	32.0	30.0
30	-	-	-	32.0	29.0	27.0	26.0
34	-	-	-	-	23.0	21.0	19.0
38	-	-	-	-	18.0	16.0	14.0
42	-	-	-	-	-	13.0	10.0
46	-	-	-	-	-	-	7.0
No. of Hoist Lines	**2x13	**2x15	**2x14	**2x14			
	*2x11	*2x11	*2x11	*2x11	*2x11	*2x11	*2x9
	1x11	1x11	1x11	1x11	1x11	1x11	1x11
	**0111	**0112	**0113	**0114			
	*0181	*0182	*0183	*0184	*0185	*0186	*0187
DS	0161	0162	0163	0164	0165	0166	0167

DS = operating mode switch on PAT-console

\*\*/\*double hook block required!

CC 2600 Capacities on Main Boom

SH
----

360°

Capacity (t) = Load + Hook Block

Counterweight 129 t  
Track 6.9 m

Radius (m)	Main Boom (m)		Type 717-01/714-01			
	60.0	66.0	72.0	78.0	84.0	90.0
9	211.0*	-	-	-	-	-
10	175.0*	174.0*	171.0*	-	-	-
12	128.0	127.0	126.0	125.0*	122.0*	118.0*
14	100.0	98.0	97.0	96.0	95.0	92.0
16	80.0	78.0	78.0	76.0	76.0	74.0
18	66.0	64.0	63.0	62.0	62.0	60.0
20	55.0	53.0	53.0	51.0	51.0	49.0
22	46.0	45.0	44.0	43.0	42.0	41.0
24	40.0	38.0	37.0	35.0	35.0	33.0
26	34.0	32.0	31.0	29.0	29.0	27.0
28	29.0	27.0	26.0	24.0	24.0	22.0
30	25.0	23.0	22.0	20.0	20.0	18.0
34	18.0	16.0	15.0	13.0	13.0	11.0
38	13.0	11.0	10.0	8.0	8.0	6.0
42	9.0	7.0	6.0	-	-	-
46	6.0	-	-	-	-	-
No. of Hoist Lines						
	*2x9	*2x7	*2x7	*2x5	*2x5	*2x5
	1x11	1x11	1x10	1x9	1x9	1x8
	*0188	*0189	*0190	*0191	*0192	*0193
DS	0168	0169	0170	0171	0172	0173

DS = operating mode switch on PAT-console

\*double hook block required!