

CC 2600 Capacities on Superlift

SSL/LSL

360°

Capacity (t) = Load + Hook Block

Counterweight 149 t
Track 8 m

Main Boom 108.0 m Type 717-01/714-01/617-01

SL-Mast 30.0 m Type 617-01/612-02

Mast-Radius 13.8 m

SL-Cwt.-Radius 13.0 m

Radius (m)	Superlift-Counterweight (t)					
	0.0	50.0	100.0	150.0	200.0	250.0
16	107.0*	120.0*	-	-	-	-
18	90.0	120.0*	-	-	-	-
20	76.0	116.0*	120.0*	-	-	-
22	65.0	100.0*	120.0*	-	-	-
24	56.0	88.0	119.0*	-	-	-
26	49.0	77.0	106.0*	120.0*	-	-
28	43.0	69.0	95.0*	120.0*	-	-
30	37.0	62.0	85.0	109.0*	-	-
34	29.0	50.0	71.0	91.0	112.0*	-
38	22.0	41.0	59.0	78.0	96.0*	-
42	16.0	34.0	51.0	67.0	83.0	99.0*
46	12.0	28.0	43.0	58.0	73.0	88.0
50	9.0	23.0	37.0	51.0	64.0	78.0
54	6.0	19.0	32.0	45.0	57.0	70.0
58	-	15.0	27.0	40.0	51.0	63.0
62	-	12.0	24.0	35.0	46.0	57.0
66	-	10.0	20.0	31.0	42.0	52.0
70	-	7.0	17.0	27.0	37.0	47.0
74	-	6.0	15.0	24.0	34.0	43.0
78	-	-	13.0	22.0	31.0	39.0
82	-	-	11.0	19.0	28.0	36.0
86	-	-	9.0	17.0	25.0	33.0
90	-	-	8.0	15.0	23.0	31.0
94	-	-	6.0	14.0	21.0	28.0

No. of Hoist Lines *2 x 5
1 x 7

	*2741	*2751	*2761	*2771	*2781	*2785
DS	2941	2951	2961	2971	2981	2985

DS = operating mode switch on PAT-console

* double hook block required

CC 2600 Capacities on Superlift

SSL/LSL

360°

Capacity (t) = Load + Hook Block

Counterweight 149 t
Track 8 m

Main Boom 120.0 m Type 717-01/714-01/617-01

SL-Mast 30.0 m Type 617-01/612-02

Mast-Radius 13.8 m

SL-Cwt.-Radius 13.0 m

Radius (m)	Superlift-Counterweight (t)					
	0.0	50.0	100.0	150.0	200.0	250.0
18	86.0*	90.0*	-	-	-	-
20	73.0	90.0*	-	-	-	-
22	62.0	88.0*	-	-	-	-
24	53.0	85.0*	85.0*	-	-	-
26	46.0	77.0	82.0*	-	-	-
28	40.0	69.0	80.0*	-	-	-
30	35.0	61.0	77.0	-	-	-
34	27.0	50.0	70.0	72.0	-	-
38	21.0	41.0	59.0	68.0	-	-
42	15.0	33.0	50.0	64.0	-	-
46	11.0	27.0	43.0	58.0	60.0	-
50	8.0	22.0	37.0	50.0	57.0	-
54	5.0	18.0	31.0	44.0	54.0	-
58	-	15.0	27.0	39.0	51.0	-
62	-	12.0	23.0	34.0	45.0	48.0
66	-	9.0	20.0	30.0	41.0	46.0
70	-	7.0	17.0	27.0	37.0	44.0
74	-	5.0	14.0	23.0	33.0	42.0
78	-	-	12.0	21.0	30.0	38.0
82	-	-	10.0	18.0	27.0	35.0
86	-	-	8.0	16.0	24.0	32.0
90	-	-	6.0	14.0	22.0	29.0
94	-	-	5.0	12.0	19.0	27.0
98	-	-	-	10.0	17.0	25.0
102	-	-	-	9.0	16.0	22.0
106	-	-	-	8.0	14.0	21.0

No. of Hoist Lines *2 x 4
1 x 6

	*2742	*2752	*2762	*2772	*2782	*2786
DS	2942	2952	2962	2972	2982	2986

DS = operating mode switch on PAT-console

* double hook block required