

CC 2600 Capacities on 6-m-Runner SH / SSL 360°
 Capacity (t) = Load + Hook Block Counterweight 149 / 129 t¹⁾
 Track 8 m

Radius (m)	Main Boom (m)		Type 717-01/714-01				
	18.0	24.0	30.0	36.0	42.0	48.0	54.0
7	25.0	-	-	-	-	-	-
8	25.0	25.0	-	-	-	-	-
9	25.0	25.0	25.0	25.0	-	-	-
10	25.0	25.0	25.0	25.0	25.0	25.0	-
12	25.0	25.0	25.0	25.0	25.0	25.0	25.0
14	25.0	25.0	25.0	25.0	25.0	25.0	25.0
16	25.0	25.0	25.0	25.0	25.0	25.0	25.0
18	25.0	25.0	25.0	25.0	25.0	25.0	25.0
20	-	25.0	25.0	25.0	25.0	25.0	25.0
22	-	25.0	25.0	25.0	25.0	25.0	25.0
24	-	-	25.0	25.0	25.0	25.0	25.0
26	-	-	25.0	25.0	25.0	25.0	25.0
28	-	-	25.0	25.0	25.0	25.0	25.0
30	-	-	-	25.0	25.0	25.0	25.0
34	-	-	-	-	23.0	21.0	23.0
38	-	-	-	-	18.0	16.0	17.0
42	-	-	-	-	-	11.0	12.0
46	-	-	-	-	-	-	8.0

No. of Hoist Lines 2

DS	SH	6001	6002	6003	6004	6005	6006	6007
DS	SSL						6104	6105
	MR	15 m						

DS = operating mode switch on PAT-console / MR = Mast-Radius

Areas of Validity

SH : main boom lengths 18 - 90 m
 SSL: main boom lengths 48 - 90 m, superlift-counterweight has to be 0 t

¹⁾ SH : main boom lengths 18 - 30 m

Hoist III has to be used for runner operation on principle. A double hook block of 8.5 t and a single hook block of 5.5 t respectively on main boom head are part of the SLI-programming.

CC 2600 Capacities on 6-m-Runner

SH / SSL

360°

Capacity (t) = Load + Hook Block

Counterweight 149 t
Track 8 m

Radius (m)	Main Boom (m)		Type 717-01/714-01			
	60.0	66.0	72.0	78.0	84.0	90.0
12	25.0	-	-	-	-	-
14	25.0	25.0	25.0	-	-	-
16	25.0	25.0	25.0	25.0	25.0	25.0
18	25.0	25.0	25.0	25.0	25.0	25.0
20	25.0	25.0	25.0	25.0	25.0	25.0
22	25.0	25.0	25.0	25.0	25.0	25.0
24	25.0	25.0	25.0	25.0	25.0	25.0
26	25.0	25.0	25.0	25.0	25.0	25.0
28	25.0	25.0	25.0	25.0	25.0	25.0
30	25.0	25.0	25.0	25.0	24.0	23.0
34	21.0	20.0	19.0	17.0	16.0	15.0
38	15.0	14.0	12.0	11.0	10.0	8.0
42	10.0	9.0	7.0	6.0	4.0	3.0
46	6.0	5.0	3.0	-	-	-
50	3.0	-	-	-	-	-

No. of Hoist Lines

2

DS SH	6008	6009	6010	6011	6012	6013
DS SSL	6106	6107	6108	6109	6110	6111
MR 15 m						

DS = operating mode switch on PAT-console / MR = Mast-Radius

Areas of Validity

SH : main boom lengths 18 - 90 m
SSL: main boom lengths 48 - 90 m, superlift-counterweight has to be 0 t

Hoist III has to be used for runner operation on principle. A double hook block of 8.5 t and a single hook block of 5.5 t respectively on main boom head are part of the SLI-programming.